## Missouri Department of Natural Resources



#### PUBLIC NOTICE

#### DRAFT MISSOURI STATE OPERATING PERMIT

DATE: September 29, 2006

In accordance with the state Clean Water Law, Chapter 644, RSMo, Clean Water Commission regulation 10 CSR 20-6.010, and the federal Clean Water Act, the applicants listed herein have applied for authorization to either discharge to waters of the state or to operate a no-discharge wastewater treatment facility. The proposed permits for these operations are consistent with applicable water quality standards, effluent standards and/or treatment requirements or suitable timetables to meet these requirements (see 10 CSR 20-7.015 and 7.031). All permits will be issued for a period of five years, unless noted otherwise in the Public Notice for that discharge.

On the basis of preliminary staff review and the application of applicable standards and regulations, the Missouri Department of Natural Resources (MDNR), as administrative agent for the Missouri Clean Water Commission, proposes to issue a permit(s) subject to certain effluent limitations, schedules, and special conditions. The proposed determinations are tentative pending public comment.

Persons wishing to comment on the proposed permit conditions are invited to submit them in writing to the Department of Natural Resources, Water Protection Program, P.O. Box 176, Jefferson City, Missouri 65102, ATTN: NPDES Permits and Engineering Section / Permit Comments. **Please include the permit number in all comment letters.** 

Comments should be confined to the issues relating to the proposed action and permit(s) and the effect on water quality. The MDNR may not consider as relevant comments or objections to a permit based on issues outside the authority of the Clean Water Commission, (see <u>Curdt v. Mo. Clean Water Commission</u>, 586 S.W.2d 58 Mo. App. 1979).

All comments must be postmarked by October 30, 2006 or received in our office by 5:00 p.m. on November 2, 2006. The requirement of a signed document makes it impossible to accept email comments for consideration at this time. Comments will be considered in the formulation of all final determinations regarding the applications. If response to this notice indicates significant public interest, a public meeting or hearing may be held after due notice for the purpose of receiving public comment on the proposed permit or determination. Public hearings and/or issuance of the permit will be conducted or processed according to 10 CSR 20-6.020.

Copies of all draft permits and other information including copies of applicable regulations are available for inspection and copying at DNR's website, http://www.dnr.mo.gov/env/wpp/index.html, or at the Department of Natural Resources, Water Protection Program, P.O. Box 176, Jefferson City, Missouri 65102, between the hours of 8:00 a.m. and 5:00 p.m., Monday through Friday.

Public Notice Date: September 29, 2006 Permit Number: MO-0028738 Northeast Regional Office					
FACILITY NAME AND ADDRESS	NAME AND ADDRESS OF OWNER				
Brookfeld Southwest WWTF West of Highway 11, Brookfield, MO 64628	City of Brookfield 116 West Brooks, Brookfield, MO 64628				
RECEIVING STREAM & LEGAL DESCRIPTION	TYPE OF DISCHARGE				
Receiving Stream: Elk Creek (U) Legal Description: SE ¼, Sec. 12, T57N, R20W, Linn County Latitude/Longitude: +3946081/-09305120					

#### STATE OF MISSOURI

### DEPARTMENT OF NATURAL RESOURCES



MISSOURI STATE OPERATING PERMIT

In compliance with the Missouri Clean Water Law, (Chapter 644 R.S. Mo. as amended, hereinafter, the Law), and the Federal Water Pollution Control Act (Public Law 92 500, 92 Congress) as amended,

Permit No. MO-0028738

Owner: City of Brookfield

Address: 116 West Brooks, Brookfield, MO 64628

Continuing Authority: Same as above Address: Same as above

Facility Name: Brookfeld Southwest WWTF

Address: West of Highway 11, Brookfield, MO 64628

Legal Description: SE ¼, Sec. 12, T57N, R20W, Linn County

Latitude/Longitude: +3946081/-09305120

Receiving Stream: Elk Creek (U)
First Classified Stream and ID: Elk Creek (C) (0604)
USGS Basin & Sub-watershed No.: (10280103 – 140002)

is authorized to discharge from the facility described herein, in accordance with the effluent limitations and monitoring requirements as set forth herein:

#### **FACILITY DESCRIPTION**

Outfall #001 - POTW - SIC #4952

Three cell aerated lagoon/sludge is retained in lagoon.

Design population equivalent is 4,000.

Design flow is 0.4 MGD.

Actual flow is 0.25 MGD.

Design sludge production is 60 dry tons/year.

This permit authorizes only wastewater discharges under the Missouri Clean Water Law and the National Pollutant Discharge Elimination System; it does not apply to other regulated areas. This permit may be appealed in accordance with Section 644.051.6 of the Law.

Effective Date	Doyle Childers, Director, Department of Natural Resources Executive Secretary, Clean Water Commission
	Edward Callerith Director of Stoff Clean Water Commission
Expiration Date MO 780-0041 (10-93)	Edward Galbraith, Director of Staff, Clean Water Commission

# A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS PAGE NUMBER 2 of 7 PERMIT NUMBER MO-0028738

The permittee is authorized to discharge from outfall(s) with serial number(s) as specified in the application for this permit. The final effluent limitations shall become effective upon issuance and remain in effect until expiration of the permit. Such discharges shall be controlled, limited and monitored by the permittee as specified below:

OUTE ALL MUMBER AND FEET HENT		FINAL EFFLUENT LIMITATIONS MONITORING REQUIREMENTS				
OUTFALL NUMBER AND EFFLUENT PARAMETER(S)	UNITS	DAILY MAXIMUM	WEEKLY AVERAGE	MONTHLY AVERAGE	MEASUREMENT FREQUENCY	SAMPLE TYPE
Outfall #001						
Flow	MGD	*		* \	once/month	24 hr. total
Biochemical Oxygen Demand <sub>5</sub> ***	mg/L		63	45	once/month	grab
Total Suspended Solids***	mg/L		<b>120</b>	80	once/month	grab
pH – Units	SU			****	once/month	grab
Oil & Grease	mgL	15		10	once/month	grab
Ammonia as N	mg/L	*		*	once/month	grab

MONITORING REPORTS SHALL BE SUBMITTED MONTHLY; THE FIRST REPORT IS DUE \_\_\_\_\_\_ DISCHARGE OF FLOATING SOLIDS OR VISIBLE FOAM IN OTHER THAN TRACE AMOUNTS.

. THERE SHALL BE NO

#### B. STANDARD CONDITIONS

IN ADDITION TO SPECIFIED CONDITIONS STATED HEREIN, THIS PERMIT IS SUBJECT TO THE ATTACHED Parts I, II & III STANDARD CONDITIONS DATED October 1, 1980 and August 15, 1994, AND HEREBY INCORPORATED AS THOUGH FULLY SET FORTH HEREIN.

MO 780-0010 (8/91)

#### A. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS (continued)

- \* Monitoring requirement only.
- \*\* Sample once per month during the months of .
- \*\*\* This facility is required to meet a removal efficiency of 65% or more.
- \*\*\*\* pH is measured in pH units and is not to be averaged. The pH is to be maintained at or above 6.0 pH units.

#### C. SPECIAL CONDITIONS

- 1. This permit may be reopened and modified, or alternatively revoked and reissued, to:
  - (a) Comply with any applicable effluent standard or limitation issued or approved under Sections 301(b)(2)(C) and (D), 304(b)(2), and 307(a) (2) of the Clean Water Act, if the effluent standard or limitation so issued or approved:
    - (1) contains different conditions or is otherwise more stringent than any effluent limitation in the permit; or
    - (2) controls any pollutant not limited in the permit.
  - (b) Incorporate new or modified effluent limitations or other conditions, if the result of a waste load allocation study, toxicity test or other information indicates changes are necessary to assure compliance with Missouri's Water Quality Standards.
  - (c) Incorporate new or modified effluent limitations or other conditions if, as the result of a watershed analysis, a Total Maximum Daily Load (TMDL) limitation is developed for the receiving waters which are currently included in Missouri's list of waters of the state not fully achieving the state's water quality standards, also called the 303(d) list.

The permit as modified or reissued under this paragraph shall also contain any other requirements of the Clean Water Act then applicable.

2. All outfalls must be clearly marked in the field.

- 3. Permittee will cease discharge by connection to areawide wastewater treatment system within 90 days of notice of its availability.
- 4. Changes in Discharges of Toxic Substances

The permittee shall notify the Director as soon as it knows or has reason to believe:

- That any activity has occurred or will occur which would result in the discharge of any toxic pollutant which is not limited in the permit, if that discharge will exceed the highest of the following "hotification levels:"
  - One hundred micrograms per liter (100 µg/L),
  - (2) Two hundred micrograms per liter (200 µg/L) for acrolein and acrylonitrile; five hundred micrograms per liter  $(500 \ \mu g/L)$  for 2,5 dinitrophenol and for 2-methy 4, 6-din trophenol; and one milligram per liter  $(1 \ mg/L)$  for antimonv:
  - Five (5) times the maximum concentration value reported for the pollutant in the permit application; The level established in Part A of the permit by the Director. (3)
- That they have begun or expect to begin to use of manufacture as an intermediate or final product or byproduct any toxic (b) pollutant, which was not reported in the permit application.
- That the effluent limit established in part A of the permit will be exceeded.
- Report as no-discharge when a discharge does not occur during the report period. 5.

#### 6. Water Quality Standards

- Discharges to waters of the state shall not cause a violation of water quality standards rule under 10 CSR 20-7.031, including both specific and general criteria.
- (b) General Criteria. The following general water quality criteria shall be applicable to all waters of the state at all times including mixing zones. No water contaminant, by itself or in combination with other substances, shall prevent the waters of the state from meeting the following conditions:
  - Waters shall be free from substances in sufficient amounts to cause the formation of putrescent, unsightly or harmful bottom deposits or prevent full maintenance of beneficial uses;
  - Waters shall be free from oil, scum and floating debris in sufficient amounts to be unsightly or prevent full (2) maintenance of beneficial uses;
  - Waters shall be free from substances in sufficient amounts to cause unsightly color or turbidity, offensive odor or (3) prevent full maintenance of beneficial uses;
  - (4) Waters shall be free from substances or conditions in sufficient amounts to result in toxicity to human, animal or aquatic life;
  - There shall be no significant human health hazard from incidental contact with the water; (5)
  - (6) There shall be no acute toxicity to livestock or wildlife watering;
  - (7) Waters shall be free from physical, chemical or hydrologic changes that would impair the natural biological community:
  - (8) Waters shall be free from used tires, car bodies, appliances, demolition debris, used vehicles or equipment and solid waste as defined in Missouri's Solid Waste Law, section 260.200, RSMo, except as the use of such materials is specifically permitted pursuant to section 260.200-260.247.
- 7. Sludge and Biosolids Use For Domestic Wastewater Treatment Facilities
  - Permittee shall comply with the pollutant limitations, monitoring, reporting, and other requirements in accordance with the attached permit Standard Conditions.
  - If sludge is not removed by a contract hauler, permittee is authorized to land apply biosolids. Permit Standard (b) Conditions, Part III shall apply to the land application of biosolids. Permittee shall notify the department at least 180 days prior to the planned removal of biosolids. The department may require submittal of a biosolids management plan for department review and approval as determined appropriate on a case-by-case basis.

8. Whole Effluent Toxicity (WET) tests shall be conducted as follows:

SUMMARY OF WET TESTING FOR THIS PERMIT						
OUTFALL	A.E.C. %	FREQUENCY	SAMPLE TYPE	MONTH		
001	100	once/year	24 hr. Composite	August		

- (a) Test Schedule and Follow-Up Requirements
  - (1) Perform a SINGLE-dilution test in the months and at the frequency specified above. For tests which are successfully passed, submit test results USING THE DEPARTMENT'S WET TEST REPORT FORM #MO-780-1899 along with complete copies of the test reports as received from the laboratory, including copies of chain-of-custody forms within 30 calendar days of availability to the WATER PROTECTION PROGRAM, P.O. Box 176, Jefferson City, MO 65102. If the effluent passes the test, do not repeat the test until the next test period.
    - (a) For discharge of stormwater, samples shall be collected within three hours from when discharge first occurs.
    - (b) Samples submitted for analysis of stormwater discharges shall be collected as a grab.
    - (c) For discharges of non-stormwater, samples shall be collected only when precipitation has not occurred for a period of forty-eight hours prior to sample collection. In no event shall sample collection occur simultaneously with the occurrence of precipitation excepting for stormwater samples.
    - (d) A twenty-four hour composite sample shall be submitted for analysis of non-stormwater discharges.
    - (e) Upstream receiving water samples, where required, shall be collected upstream from any influence of the effluent where downstream flow is clearly evident.
    - (f) Samples submitted for analysis of upstream receiving water may be collected as either a grab or twenty-four-hour composite as appropriate to the nature of the discharge.
    - (g) Chemical and physical analysis of the upstream control and effluent sample shall occur immediately upon being received by the laboratory, prior to any manipulation of the effluent sample beyond preservation methods consistent with federal guidelines for WET testing that are required to stabilize the sample during shipping.
    - (h) Any and all chemical or physical analysis of the effluent sample performed in conjunction with the WET test shall be performed at the 100% Effluent concentration in addition to analyses performed upon any other effluent concentration.
    - (i) All chemical analyses included in the Missouri Department of Natural Resources WET test report form #MO-780-1899 shall be performed and results shall be recorded in the appropriate field of the report form.
    - (j) Where flow-weighted composite sample is required for analysis, the samples shall be composited at the laboratory where the test is to be performed.
    - (k) Where in stream testing is required downstream from the discharge, sample collection shall occur immediately below the established Zone of Initial Dilution in conjunction with or immediately following a release or discharge.
    - (l) Samples submitted for analysis of downstream receiving water may be collected as either a grab or twenty-four-hour composite as appropriate to the nature of the discharge.
    - (m) All instream samples, including downstream samples, shall be tested for toxicity at the 100% concentration in addition to any other assigned AEC for in-stream samples.
  - (2) All failing test results along with complete copies of the test reports as received from the laboratory, INCLUDING THOSE TESTS CONDUCTED UNDER CONDITION (3) BELOW, shall be reported to the WATER PROTECTION PROGRAM, P.O. Box 176, Jefferson City, MO 65102 within 14 calendar days of the availability of the results.
  - (3) If the effluent fails the test, a multiple dilution test shall be performed within 30 calendar days and biweekly thereafter, until one of the following conditions are met:
    - (a) THREE CONSECUTIVE MULTIPLE-DILUTION TESTS PASS. No further tests need to be performed until next regularly scheduled test period.
    - (b) A TOTAL OF THREE MULTIPLE-DILUTION TESTS FAIL.
  - (4) Failure of at least two multiple-dilution tests during any period of accelerated monitoring violates the permit narrative requirement for aquatic life protection.

- 8. Whole Effluent Toxicity tests (continued):
  - (5) The permittee shall submit a CONCISE summary of all test results for the test series to the WATER PROTECTION PROGRAM, P.O. Box 176, Jefferson City, MO 55102 within 14 calendar days of the third failed test.
  - (6) Additionally, the following shall apply upon failure of the third MULTIPLE DILUTION test: A toxicity identification evaluation (TIE) or toxicity reduction evaluation (TRE) is automatically triggered. The permittee shall contact THE WATER PROTECTION PROGRAM within 14 calendar days from availability of the test results to ascertain as to whether a TIE or TRE is appropriate. The permittee shall submit a plan for conducting a TIE or TRE to the WATER PROTECTION PROGRAM within 60 calendar days of the date of DNR's direction to perform either a TIE or TRE. This plan must be approved by DNR before the TIE or TRE is begun. A schedule for completing the TIE or TRE shall be established in the plan approval.
  - (7) Upon DNR's approval, the TIE/TRE schedule may be modified if toxicity is intermittent during the TIE/TRE investigations. A revised WRT text schedule may be established by DNR for this period.
  - (8) If a previously completed TE has clearly identified the cause of toxicity, additional TIEs will not be required as long as effluent characteristics remain essentially unchanged and the permittee is proceeding according to a DNR approved schedule to complete a TRE and reduce toxicity. Regularly scheduled WET testing as required in the permit, without the follow-up requirements, will be required during this period.
  - (9) When WET test sampling is required to run over one DMR period, each DMR report shall contain a copy of the Department's WET test report form that was generated during the reporting period.
  - (10) Submit a concise summary in tabular format of all test results with the annual report.
  - (b) PASS/FAIL procedure and effluent limitations:
    - (1) To pass a single-dilution test, mortality observed in the AEC test concentration shall not be significantly different (at the 95% confidence level; p = 0.05) than that observed in the upstream receiving-water control sample. Where upstream receiving water is not available mortality observed in the AEC test concentration shall not be significantly different (at the 95% confidence level; p = 0.05) than that observed in the laboratory control. The appropriate statistical tests of significance shall be consistent with the most current edition of METHODS FOR MEASURING THE ACUTE TOXICITY OF EFFLUENTS AND RECEIVING WATERS TO FRESHWATER AND MARINE ORGANISMS or other Federal guidelines as appropriate or required.
    - (2) To pass a multiple-dilution test:
      - (a) For facilities with a computed percent effluent at the edge of the zone of initial dilution, Allowable Effluent Concentration (AEC), OF 30% OR LESS THE AEC must be less than three-tenths (0.3) of the LC<sub>50</sub> concentration for the most sensitive of the test organisms; **OR**,
      - (b) For facilities with an AEC greater than 30% the LC50 concentration must be greater than 100%; **AND**,
      - all effluent concentrations equal to or less than the AEC must be nontoxic. Mortality observed in all effluent concentrations equal to or less than the AEC shall not be significantly different (at the 95% confidence level; p = 0.05) than that observed in the upstream receiving-water control sample. Where upstream receiving water is not available mortality observed in the AEC test concentration shall not be significantly different (at the 95% confidence level; p = 0.05) than that observed in the laboratory control. The appropriate statistical tests of significance shall be consistent with the most current edition of METHODS FOR MEASURING THE ACUTE TOXICITY OF EFFLUENTS AND RECEIVING WATERS TO FRESHWATER AND MARINE ORGANISMS or other federal guidelines as appropriate or required. Failure of one multiple-dilution test may be considered an effluent limit violation.

#### (c) Test Conditions

- (1) Test Type: Acute Static non-renewal
- (2) Test species: Ceriodaphnia dubia and Pimephales promelas (fathead minnow). Organisms used in WET testing shall come from cultures reared for the purpose of conducting toxicity tests and cultured in a manner consistent with the most current USEPA guidelines. All test animals shall be cultured as described in the most current edition of METHODS FOR MEASURING THE ACUTE TOXICITY OF EFFLUENTS AND RECEIVING WATERS TO FRESHWATER AND MARINE ORGANISMS.
- (3) Test period: 48 hours at the "Acceptable Effluent Concentration" (AEC) specified above.
- (4) When dilutions are required, upstream receiving stream water shall be used as dilution water. If upstream water is unavailable or if mortality in the upstream water exceeds 10%, "reconstituted" water will be used as dilution water. Procedures for generating reconstituted water will be supplied by the MDNR upon request.

8. Whole Effluent Toxicity tests (continued):

(5) Single-dilution tests will be run with:

- (a) Effluent at the AEC concentration;
- (b) 100% receiving-stream water (if available), collected up tream of the outfall at a point beyond any influence of the effluent; and
- (c) reconstituted water.
- (6) Multiple-dilution tests will be run with:
  - (a) 100%, 50%, 25%, 12.5%, and 6.25% effluent, unless the AEC is less than 25% effluent, in which case dilutions will be 4 times the AEC, two times the AEC, 1/2 AEC and 1/4 AEC;
  - (b) 100% receiving-stream water (if available), collected upstream of the outfall at a point beyond any influence of the effluent; and
  - (c) reconstituted water.
- (7) If reconstituted-water control mortality for a test species exceeds 10%, the entire test will be rerun.
- (8) If upstream control mortality exceeds 10%, the entire test will be rerun using reconstituted water as the dilutant.
- 9. All discharges of wastewater from the collection system from Sanitary Sewer Overflows (SSOs) or bypasses must be reported to the Northeast Regional Office within 24 hours of their discovery. A written report will be submitted to the regional office within 5 days of discovery of the discharge detailing quantity of wastewater discharged, duration, cause, corrective actions taken, and any planned follow-up action. SSOs and bypasses will also be sampled once per discharge event for Fecal Coliform (grab sample). Monitoring reports shall be submitted with the next monthly discharge monitoring report.

#### D. SCHEDULE OF COMPLIANCE

- 1. By January 15, 2008, submit to the Northeast Regional Office for review and approval an engineering evaluation of the collection system serving this facility. The evaluation must:
  - a. Identify all Sanitary Sewer Overflows (SSOs) and sources of inflow & infiltration in the collection system of this facility. All SSOs must be shown on a map of the city and located via latitude/longitude coordinates.
  - b. Include a study of sources and extent of inflow and infiltration (I&I) into the collection system.
  - c. Include a plan for data collection for all SSO and bypass events, including quantity, duration, cause, actions taken, and any planned follow-up action.
  - d. Identify short and long term actions to reduce or eliminate I&I.
  - e. Implementation of operational practices and maintenance/repairs.
  - f. Implementation of appropriate regulatory controls
  - g. Implementation of capitol improvements.

With the evaluation, a Corrective Action Plan (Plan) must also be submitted for review and approval. The Plan will include financial planning for capitol improvements and ongoing operational activities, and detail a quarter by quarter schedule for implementing corrective actions necessary for elimination of the SSOs and a substantial reduction in the sources of I&I. After the plan has been approved by the department, the permittee shall immediately begin implementation of the plan and proposed schedule.

In the event that initially submitted Evaluation and Plan are not acceptable, the permittee shall submit revisions within 30 days of receipt of comments from the department. In the event that revisions are necessary after initial approval, the permittee shall submit said revisions for review and approval within 30 days of request by the department.

2. Beginning on March 1, 2008, submit semi-annual progress reports to the Northeast Regional Office of efforts to eliminate SSOs and sources of I&I. These reports are due June 1<sup>st</sup> and December 1<sup>st</sup>.

#### SUMMARY OF TEST METHODOLOGY FOR WHOLE-EFFLUENT TOXICITY TESTS

Whole-effluent-toxicity test required in NPDES permits shall use the following test conditions when performing single or multiple dilution methods. Any future changes in methodology will be supplied to the permittee by the Missouri Department of Natural Resources (MDNR). Unless more stringent methods are specified by the DNR, the procedures shall be consistent with the most current edition of Methods for Measuring the Acute Toxicity of Effluents and Receiving Waters to Freshwater and Marine Organisms,

Test conditions for Ceriodaphnia dubia:

Test duration:

Temperature:

Light Quality:

Photoperiod:

Size of test vessel:

Volume of test solution:

Age of test organisms:

No. of animals/test vessel:

No. of replicates/concentration:

No. of organisms/concentration:

Feeding regime:

Aeration:

Dilution water:

Endpoint:

Test acceptability criterion:

√48 h

25 ± 13C Temperatures shall not deviate by more than 3°C during

the test.

Ambient laboratory illumination

16 h light, 8 h dark

30 mL (minimum)

15 mL (minimum)

<24 h old

5 4

20 (minimum)

None (feed prior to test)

None

Upstream receiving water; if no upstream flow, synthetic water

modified to reflect effluent hardness.

Pass/Fail (Statistically significant Mortality when compared to upstream receiving water control or synthetic control if upstream

water was not available at  $p \le 0.05$ )

90% or greater survival in controls

Test conditions for (<u>Pimephales promelas</u>):

Test duration: 48 h

Temperature:  $25 \pm 1^{\circ}\text{C}$  Temperatures shall not deviate by more than  $3^{\circ}\text{C}$  during

the test.

Light Quality: Ambient laboratory illumination

Photoperiod: 16 h light/8 h dark
Size of test vessel: 250 mL (minimum)
Volume of test solution: 200 mL (minimum)
Age of test organisms: 1-14 days (all same age)

No. of animals/test vessel:

No. of replicates/concentration: 4 (minimum) single dilution method

No. of organisms/concentration:

2 (minimum) multiple dilution method
40 (minimum) single dilution method
20 (minimum) multiple dilution method

Feeding regime: None (feed prior to test)

Aeration: None, unless DO concentration falls below 4.0 mg/L; rate should

not exceed 100 bubbles/min.

Dilution water: Upstream receiving water; if no upstream flow, synthetic water

modified to reflect effluent hardness.

Endpoint: Pass/Fail (Statistically significant Mortality when compared to

upstream receiving water control or synthetic control if upstream

water was not available at p $\leq$  0.05)

Test Acceptability criterion: 90% or greater survival in controls

Date of Fact Sheet: 9-29-06

Date of Public Notice: 9-29-06

## NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT FACT SHEET

This Fact Sheet explains the applicable regulations, rationale for development of this permit and the public participation process.

The Federal Water Pollution Control Act ("Clean Water Act" Section 402 Public Law 92-500 as amended) established the National Pollutant Discharge Elimination System (NPDES) permit program. This program regulates the discharge of pollutants from point sources into the waters of the United States, and the release of storm water from certain point sources. All such discharges are unlawful without a permit (Section 301 of the "Clean Water Act"). After a permit is obtained, a discharge not in compliance with all permit terms and conditions is unlawful. Permits in Missouri are issued by the Director of the Department of Natural Resources under an approved program, operating in accordance with federal and state laws (Federal "Clean Water Act" and "Missouri Clean Water Law" Section 644 as amended).

NPDES PERMIT NUMBER: MO-0028738

FACILITY NAME: Brookfield Southwest Wastewater Treatment Facility

OWNER NAME: City of Brookfield

LOCATION: SE ¼, Sec. 12, T57N, R20W, Linn County

RECEIVING STREAM: Elk Creek, unclassified

PURPOSE: operating permit renewal

#### FACILITY DESCRIPTION AND RATIONALE

The wastewater treatment facility is composed of a three cell aerated lagoon.

10 CSR 20-7.031 Missouri Water Quality Standards, Missouri Department of Natural Resources (the Department) "defines the Clean Water Commission water quality objectives in terms of water uses to be maintained and the criteria to protect those uses." The receiving stream's beneficial water uses to be maintained are livestock and wildlife watering, whole body contact recreation, and protection of aquatic life.

To protect these beneficial uses and the water quality of the receiving stream, effluent limitations have been established under federal and state laws. Ammonia as N monitoring has been added to determine if reasonable potential exists for exceedance of water quality standards. Effluent limits for Oil & Grease have also been added for protection of aquatic life; 10 mg/L monthly average, 15 mg/L daily maximum. All other limits have been retained from the previous permit.

The permit also includes a Schedule of Compliance for elimination of sanitary sewer overflows.

The permit will be issued for a period of <u>five</u> years.